

# proxSafe®

Where is the digital camera? Who has been using the company car? When was the technician in the building? proxSafe is the intelligent management system for keys and valuables which provides answers to your daily 'key questions'. Contactless RFID keytag technology provides reassuring reliability. The proxSafe family is modular, expandable and network ready.

## Terminal C4

The proxSafe Terminal is an easy-to-use and intelligent user interface for all proxSafe systems. It is provided together with an administrator ID-Card to setup the System.

Users can be identified via smart card and/or by PIN entry. After log-in the user selects the desired key either from a list of keys or simply by its slot number. The system will automatically guide the user to the corresponding key slot. The period for key access, the duration for holding the key as well as the maximum number of keys can be limited individually for every user. The proxSafe Terminal allows quick returning of the keys. The user only has to present the key in front of the optionally available keyTag reader in the Terminal. The Terminal will identify the key and guide the user to the right slot.

Users can obtain quick information directly at the terminal about the actual holder of a key and the list of keyTags in or out of the cabinets. Inside the proxSafe Terminal there is space for installing an optionally available Multi-Technology card reader from deister electronic. Other readers using a Wiegand/Magstripe interface can also be integrated readily. Nearly all features of the proxSafe system can be executed by the Terminal without need for PC connection.

If operated within a network the database of the Terminal will be permanently synchronized with the central proxSafe data base. This allows control of the complete system from a remote workplace. In case of a network failure the proxSafe system stays fully operational.

Even in case of a power failure the power management of the Terminal ensures that the proxSafe system keeps working as long as possible.

## Your benefits at a glance:

- **Easy Operation**
- **Multi-Technology Reader** for User Identification
- **Quick Key Return** via 125 kHz Reader
- **Intelligent Power Management**
- **Illuminated Keypad and Display**

## Terminal C4 – Intuitive and Powerful



## Technical Data

### Dimensions:

mm (inch) W x H x D 125 x 225 x 45 (4.92 x 8.86 x 1.77)

**Housing Material:** ASA

**Colour:** black

**Protection Class:** IP54

### Operating

**Temperature:** +5 °C...+50 °C  
+41°F...+122 °F

**Relative Humidity:** 5 %...95 %, non-condensing

**Keypad:** 17 keys, back-lit,  
different colors for easy use

**Display:** 4 x 20 characters, illuminated

**Languages:** various languages selectable

**Reader (Option):** Quick Key Return and User-ID

- Reader Module 125 kHz
- 13,56 MHz mifare® and 125 kHz
- 13,56 MHz LEGIC® and 125 kHz
- 13,56 MHz I-Class™ and 125 kHz
- 13,56 MHz FeliCa and 125 kHz

**Database:** 2048 keyTags  
3000 users  
7000 events (in ring memory)  
63 keyTag time profiles  
31 user time profiles